

SIMATIC S7-400H, CPU 416-5H, central processing unit for S7-400H and S7-400F/FH, 5 interfaces: 1x MPI/DP, 1x DP, 1x PN and 2 for sync modules, 16 MB memory (10 MB data/6 MB program)



| General information                         |                                          |
|---------------------------------------------|------------------------------------------|
| Product type designation                    | CPU 416-5H PN/DP                         |
| HW functional status                        | 1                                        |
| Firmware version                            | V6.0                                     |
| Product function                            |                                          |
| • Isochronous mode                          | No                                       |
| Engineering with                            |                                          |
| • Programming package                       | As of STEP 7 V5.5 SP2 with HF1           |
| CiR - Configuration in RUN                  |                                          |
| CiR synchronization time, basic load        | 100 ms                                   |
| CiR synchronization time, time per I/O byte | 0 μs                                     |
| Supply voltage                              |                                          |
| Rated value (DC)                            |                                          |
| • 24 V DC                                   | No; Power supply via system power supply |
| Input current                               |                                          |
| from backplane bus 5 V DC, typ.             | 1.6 A                                    |
| from backplane bus 5 V DC, max.             | 1.9 A                                    |
| from backplane bus 24 V DC, max.            | 150 mA; 150 mA per DP interface          |

|                                                                                                                                                                                        |                                                                                                                                                                                                                                                                |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| from interface 5 V DC, max.                                                                                                                                                            | 90 mA; At each DP interface                                                                                                                                                                                                                                    |
| <b>Power loss</b>                                                                                                                                                                      |                                                                                                                                                                                                                                                                |
| Power loss, typ.                                                                                                                                                                       | 7.5 W                                                                                                                                                                                                                                                          |
| <b>Memory</b>                                                                                                                                                                          |                                                                                                                                                                                                                                                                |
| Type of memory                                                                                                                                                                         | other                                                                                                                                                                                                                                                          |
| <b>Work memory</b>                                                                                                                                                                     |                                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>integrated</li> <li>integrated (for program)</li> <li>integrated (for data)</li> <li>expandable</li> </ul>                                      | <ul style="list-style-type: none"> <li>16 Mbyte</li> <li>6 Mbyte</li> <li>10 Mbyte</li> <li>No</li> </ul>                                                                                                                                                      |
| <b>Load memory</b>                                                                                                                                                                     |                                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>expandable FEPRM</li> <li>expandable FEPRM, max.</li> <li>integrated RAM, max.</li> <li>expandable RAM</li> <li>expandable RAM, max.</li> </ul> | <ul style="list-style-type: none"> <li>Yes; with Memory Card (FLASH)</li> <li>64 Mbyte</li> <li>1 Mbyte</li> <li>Yes</li> <li>64 Mbyte</li> </ul>                                                                                                              |
| <b>Backup</b>                                                                                                                                                                          |                                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>present</li> <li>with battery</li> <li>without battery</li> </ul>                                                                               | <ul style="list-style-type: none"> <li>Yes</li> <li>Yes; all data</li> <li>No</li> </ul>                                                                                                                                                                       |
| <b>Battery</b>                                                                                                                                                                         |                                                                                                                                                                                                                                                                |
| <b>Backup battery</b>                                                                                                                                                                  |                                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>Backup current, typ.</li> <li>Backup current, max.</li> <li>Backup time, max.</li> <li>Feeding of external backup voltage to CPU</li> </ul>     | <ul style="list-style-type: none"> <li>180 <math>\mu</math>A; Valid up to 40°C</li> <li>1 000 <math>\mu</math>A</li> <li>Dealt with in the module data manual with the secondary conditions and the factors of influence</li> <li>5 V DC to 15 V DC</li> </ul> |
| <b>CPU processing times</b>                                                                                                                                                            |                                                                                                                                                                                                                                                                |
| for bit operations, typ.                                                                                                                                                               | 12.5 ns                                                                                                                                                                                                                                                        |
| for word operations, typ.                                                                                                                                                              | 12.5 ns                                                                                                                                                                                                                                                        |
| for fixed point arithmetic, typ.                                                                                                                                                       | 12.5 ns                                                                                                                                                                                                                                                        |
| for floating point arithmetic, typ.                                                                                                                                                    | 25 ns                                                                                                                                                                                                                                                          |
| <b>CPU-blocks</b>                                                                                                                                                                      |                                                                                                                                                                                                                                                                |
| <b>DB</b>                                                                                                                                                                              |                                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>Number, max.</li> <li>Size, max.</li> </ul>                                                                                                     | <ul style="list-style-type: none"> <li>16 000; Number range: 1 to 16000</li> <li>64 kbyte</li> </ul>                                                                                                                                                           |
| <b>FB</b>                                                                                                                                                                              |                                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>Number, max.</li> <li>Size, max.</li> </ul>                                                                                                     | <ul style="list-style-type: none"> <li>8 000; Number range: 0 to 7999</li> <li>64 kbyte</li> </ul>                                                                                                                                                             |
| <b>FC</b>                                                                                                                                                                              |                                                                                                                                                                                                                                                                |

|                                               |                                          |
|-----------------------------------------------|------------------------------------------|
| • Number, max.                                | 8 000; Number range: 0 to 7999           |
| • Size, max.                                  | 64 kbyte                                 |
| <b>OB</b>                                     |                                          |
| • Number, max.                                | see instruction list                     |
| • Size, max.                                  | 64 kbyte                                 |
| • Number of free cycle OBs                    | 1; OB 1                                  |
| • Number of time alarm OBs                    | 8; OB 10-17                              |
| • Number of delay alarm OBs                   | 4; OB 20-23                              |
| • Number of cyclic interrupt OBs              | 9; OB 30-38                              |
| • Number of process alarm OBs                 | 8; OB 40-47                              |
| • Number of DPV1 alarm OBs                    | 3; OB 55-57                              |
| • Number of startup OBs                       | 2; OB 100, 102                           |
| • Number of asynchronous error OBs            | 9; OB 80-88                              |
| • Number of synchronous error OBs             | 2; OB 121, 122                           |
| <b>Nesting depth</b>                          |                                          |
| • per priority class                          | 24                                       |
| • additional within an error OB               | 2                                        |
| <b>Counters, timers and their retentivity</b> |                                          |
| <b>S7 counter</b>                             |                                          |
| • Number                                      | 2 048                                    |
| <b>Retentivity</b>                            |                                          |
| — adjustable                                  | Yes                                      |
| — lower limit                                 | 0                                        |
| — upper limit                                 | 2 047                                    |
| — preset                                      | Z 0 to Z 7                               |
| <b>Counting range</b>                         |                                          |
| — lower limit                                 | 0                                        |
| — upper limit                                 | 999                                      |
| <b>IEC counter</b>                            |                                          |
| • present                                     | Yes                                      |
| • Type                                        | SFB                                      |
| • Number                                      | Unlimited (limited only by RAM capacity) |
| <b>S7 times</b>                               |                                          |
| • Number                                      | 2 048                                    |
| <b>Retentivity</b>                            |                                          |
| — adjustable                                  | Yes                                      |
| — lower limit                                 | 0                                        |
| — upper limit                                 | 2 047                                    |
| — preset                                      | No times retentive                       |
| <b>Time range</b>                             |                                          |
| — lower limit                                 | 10 ms                                    |

|                                              |                                                     |
|----------------------------------------------|-----------------------------------------------------|
| — upper limit                                | 9 990 s                                             |
| <b>IEC timer</b>                             |                                                     |
| • present                                    | Yes                                                 |
| • Type                                       | SFB                                                 |
| • Number                                     | Unlimited (limited only by RAM capacity)            |
| <b>Data areas and their retentivity</b>      |                                                     |
| retentive data area in total                 | Total working and load memory (with backup battery) |
| <b>Flag</b>                                  |                                                     |
| • Number, max.                               | 16 384 byte                                         |
| • Retentivity available                      | Yes                                                 |
| • Retentivity preset                         | MB 0 to MB 15                                       |
| • Number of clock memories                   | 8; in 1 memory byte                                 |
| <b>Local data</b>                            |                                                     |
| • adjustable, max.                           | 64 kbyte                                            |
| • preset                                     | 32 kbyte                                            |
| <b>Address area</b>                          |                                                     |
| <b>I/O address area</b>                      |                                                     |
| • Inputs                                     | 16 kbyte                                            |
| • Outputs                                    | 16 kbyte                                            |
| <b>Process image</b>                         |                                                     |
| • Inputs, adjustable                         | 16 kbyte                                            |
| • Outputs, adjustable                        | 16 kbyte                                            |
| • Inputs, default                            | 1 024 byte                                          |
| • Outputs, default                           | 1 024 byte                                          |
| • consistent data, max.                      | 244 byte                                            |
| • Access to consistent data in process image | Yes                                                 |
| <b>Subprocess images</b>                     |                                                     |
| • Number of subprocess images, max.          | 15                                                  |
| <b>Digital channels</b>                      |                                                     |
| • Inputs                                     | 131 072                                             |
| — of which central                           | 131 072                                             |
| • Outputs                                    | 131 072                                             |
| — of which central                           | 131 072                                             |
| <b>Analog channels</b>                       |                                                     |
| • Inputs                                     | 8 192                                               |
| — of which central                           | 8 192                                               |
| • Outputs                                    | 8 192                                               |
| — of which central                           | 8 192                                               |
| <b>Hardware configuration</b>                |                                                     |
| Number of expansion units, max.              | 21                                                  |
| connectable OPs                              | 95                                                  |

|                                                     |                                                                                                                   |
|-----------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Multicomputing                                      | No                                                                                                                |
| <b>Interface modules</b>                            |                                                                                                                   |
| • Number of connectable IMs (total), max.           | 6                                                                                                                 |
| • Number of connectable IM 460s, max.               | 6                                                                                                                 |
| • Number of connectable IM 463s, max.               | 4; Single mode only                                                                                               |
| <b>Number of DP masters</b>                         |                                                                                                                   |
| • integrated                                        | 2                                                                                                                 |
| • via CP                                            | 10; CP 443-5 Extended                                                                                             |
| • Mixed mode IM + CP permitted                      | No                                                                                                                |
| • via interface module                              | 0                                                                                                                 |
| <b>Number of IO Controllers</b>                     |                                                                                                                   |
| • integrated                                        | 1                                                                                                                 |
| • via CP                                            | 0                                                                                                                 |
| <b>Number of operable FMs and CPs (recommended)</b> |                                                                                                                   |
| • FM                                                | See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections |
| • CP, PtP                                           | See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections |
| • PROFIBUS and Ethernet CPs                         | 14; Of which max. 10 CP as DP master                                                                              |
| <b>Slots</b>                                        |                                                                                                                   |
| • required slots                                    | 2                                                                                                                 |
| <b>Time of day</b>                                  |                                                                                                                   |
| <b>Clock</b>                                        |                                                                                                                   |
| • Hardware clock (real-time)                        | Yes                                                                                                               |
| • retentive and synchronizable                      | Yes                                                                                                               |
| • Resolution                                        | 1 ms                                                                                                              |
| • Deviation per day (buffered), max.                | 1.7 s; Power off                                                                                                  |
| • Deviation per day (unbuffered), max.              | 8.6 s; Power on                                                                                                   |
| <b>Operating hours counter</b>                      |                                                                                                                   |
| • Number                                            | 16                                                                                                                |
| • Number/Number range                               | 0 to 15                                                                                                           |
| • Range of values                                   | SFCs 2, 3 and 4: 0 to 32767 hours SFC 101: 0 to 2 <sup>31</sup> - 1 hours                                         |
| • Granularity                                       | 1 h                                                                                                               |
| • retentive                                         | Yes                                                                                                               |
| <b>Clock synchronization</b>                        |                                                                                                                   |
| • supported                                         | Yes                                                                                                               |
| • to MPI, master                                    | Yes                                                                                                               |
| • to MPI, slave                                     | Yes                                                                                                               |
| • to DP, master                                     | Yes                                                                                                               |
| • to DP, slave                                      | Yes                                                                                                               |
| • in AS, master                                     | Yes                                                                                                               |
| • in AS, slave                                      | Yes                                                                                                               |

|                                                         |                |
|---------------------------------------------------------|----------------|
| • on Ethernet via NTP                                   | Yes; As client |
| <b>Time difference in system when synchronizing via</b> |                |
| • Ethernet, max.                                        | 10 ms; Via NTP |
| • MPI, max.                                             | 200 ms         |

|                             |                          |
|-----------------------------|--------------------------|
| <b>Interfaces</b>           |                          |
| Number of RS 485 interfaces | 2                        |
| Number of other interfaces  | 2; Fiber-optic interface |
| Optical interface           | No                       |

|                                                 |                         |
|-------------------------------------------------|-------------------------|
| <b>1. Interface</b>                             |                         |
| Interface type                                  | Integrated              |
| Physics                                         | RS 485 / PROFIBUS + MPI |
| Isolated                                        | Yes                     |
| Power supply to interface (15 to 30 V DC), max. | 150 mA                  |

|                      |     |
|----------------------|-----|
| <b>Protocols</b>     |     |
| • MPI                | Yes |
| • PROFIBUS DP master | Yes |
| • PROFIBUS DP slave  | No  |

|                           |                                                                                                                   |
|---------------------------|-------------------------------------------------------------------------------------------------------------------|
| <b>MPI</b>                |                                                                                                                   |
| • Number of connections   | 44; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1 |
| • Transmission rate, max. | 12 Mbit/s                                                                                                         |

|                               |     |
|-------------------------------|-----|
| <b>Services</b>               |     |
| — PG/OP communication         | Yes |
| — Routing                     | Yes |
| — Global data communication   | No  |
| — S7 basic communication      | No  |
| — S7 communication            | Yes |
| — S7 communication, as client | Yes |
| — S7 communication, as server | Yes |

|                               |                                                                                                                   |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------|
| <b>PROFIBUS DP master</b>     |                                                                                                                   |
| • Number of connections, max. | 32; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1 |
| • Transmission rate, max.     | 12 Mbit/s                                                                                                         |
| • Number of DP slaves, max.   | 32                                                                                                                |

|                               |     |
|-------------------------------|-----|
| <b>Services</b>               |     |
| — PG/OP communication         | Yes |
| — Routing                     | Yes |
| — Global data communication   | No  |
| — S7 basic communication      | No  |
| — S7 communication            | Yes |
| — S7 communication, as client | Yes |

|                                                       |                                     |
|-------------------------------------------------------|-------------------------------------|
| — S7 communication, as server                         | Yes                                 |
| — Equidistance                                        | No                                  |
| — Isochronous mode                                    | No                                  |
| — SYNC/FREEZE                                         | No                                  |
| — Activation/deactivation of DP slaves                | No                                  |
| — Direct data exchange (slave-to-slave communication) | No                                  |
| — DPV1                                                | Yes                                 |
| <b>Address area</b>                                   |                                     |
| — Inputs, max.                                        | 2 kbyte                             |
| — Outputs, max.                                       | 2 kbyte                             |
| <b>User data per DP slave</b>                         |                                     |
| — User data per DP slave, max.                        | 244 byte                            |
| — Inputs, max.                                        | 244 byte                            |
| — Outputs, max.                                       | 244 byte                            |
| — Slots, max.                                         | 244                                 |
| — per slot, max.                                      | 128 byte                            |
| <b>PROFIBUS DP slave</b>                              |                                     |
| • Number of connections                               | No configuration of CPU as DP slave |
| <b>2. Interface</b>                                   |                                     |
| Interface type                                        | PROFINET                            |
| Physics                                               | Ethernet RJ45                       |
| Isolated                                              | Yes                                 |
| automatic detection of transmission rate              | Yes; Autosensing                    |
| Autonegotiation                                       | Yes                                 |
| Autocrossing                                          | Yes                                 |
| Change of IP address at runtime, supported            | No                                  |
| Number of connection resources                        | 96                                  |
| <b>Interface types</b>                                |                                     |
| • Number of ports                                     | 2                                   |
| • integrated switch                                   | Yes                                 |
| <b>Protocols</b>                                      |                                     |
| • PROFINET IO Controller                              | Yes                                 |
| • PROFINET IO Device                                  | No                                  |
| • PROFINET CBA                                        | No                                  |
| • PROFIBUS DP master                                  | No                                  |
| • PROFIBUS DP slave                                   | No                                  |
| • Open IE communication                               | Yes                                 |
| • Web server                                          | No                                  |
| • Point-to-point connection                           | No                                  |
| • Media redundancy                                    | Yes                                 |
| <b>PROFINET IO Controller</b>                         |                                     |

|                                                                   |                                                                                                                           |
|-------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| • Transmission rate, max.                                         | 100 Mbit/s                                                                                                                |
| <b>Services</b>                                                   |                                                                                                                           |
| — PG/OP communication                                             | Yes                                                                                                                       |
| — S7 routing                                                      | Yes                                                                                                                       |
| — S7 communication                                                | Yes                                                                                                                       |
| — Isochronous mode                                                | No                                                                                                                        |
| — Shared device                                                   | Yes; Single mode only                                                                                                     |
| — Prioritized startup                                             | No                                                                                                                        |
| — Number of connectable IO Devices, max.                          | 256; In redundant mode via both interfaces                                                                                |
| — Number of connectable IO Devices for RT, max.                   | 256                                                                                                                       |
| — of which in line, max.                                          | 256                                                                                                                       |
| — Activation/deactivation of IO Devices                           | No                                                                                                                        |
| — IO Devices changing during operation (partner ports), supported | No                                                                                                                        |
| — Device replacement without swap medium                          | Yes                                                                                                                       |
| — Send cycles                                                     | 250 µs, 500 µs, 1 ms, 2 ms, 4 ms                                                                                          |
| — Updating time                                                   | 250 µs to 512 ms, minimum value depends on the number of configured user data and the configured single or redundant mode |
| <b>Address area</b>                                               |                                                                                                                           |
| — Inputs, max.                                                    | 8 kbyte                                                                                                                   |
| — Outputs, max.                                                   | 8 kbyte                                                                                                                   |
| — User data consistency, max.                                     | 1 024 byte                                                                                                                |
| <b>Open IE communication</b>                                      |                                                                                                                           |
| • Number of connections, max.                                     | 94                                                                                                                        |
| • Local port numbers used at the system end                       | 0, 20, 21, 25, 102, 135, 161, 34962, 34963, 34964, 65532, 65533, 65534, 65535                                             |
| • Keep-alive function, supported                                  | Yes                                                                                                                       |
| <b>3. Interface</b>                                               |                                                                                                                           |
| Interface type                                                    | Integrated                                                                                                                |
| Physics                                                           | RS 485 / PROFIBUS                                                                                                         |
| Power supply to interface (15 to 30 V DC), max.                   | 150 mA                                                                                                                    |
| Number of connection resources                                    | 32                                                                                                                        |
| <b>Protocols</b>                                                  |                                                                                                                           |
| • PROFIBUS DP master                                              | Yes                                                                                                                       |
| • PROFIBUS DP slave                                               | No                                                                                                                        |
| <b>PROFIBUS DP master</b>                                         |                                                                                                                           |
| • Number of connections, max.                                     | 32                                                                                                                        |
| • Transmission rate, max.                                         | 12 Mbit/s                                                                                                                 |
| • Number of DP slaves, max.                                       | 125                                                                                                                       |
| <b>Services</b>                                                   |                                                                                                                           |
| — PG/OP communication                                             | Yes                                                                                                                       |



|                                                       |     |
|-------------------------------------------------------|-----|
| — Routing                                             | Yes |
| — Global data communication                           | No  |
| — S7 basic communication                              | No  |
| — S7 communication                                    | Yes |
| — S7 communication, as client                         | Yes |
| — S7 communication, as server                         | Yes |
| — Equidistance                                        | No  |
| — Isochronous mode                                    | No  |
| — SYNC/FREEZE                                         | No  |
| — Activation/deactivation of DP slaves                | No  |
| — Direct data exchange (slave-to-slave communication) | No  |
| — DPV0                                                | Yes |
| — DPV1                                                | Yes |

#### Address area

|                 |         |
|-----------------|---------|
| — Inputs, max.  | 8 kbyte |
| — Outputs, max. | 8 kbyte |

#### User data per DP slave

|                                |          |
|--------------------------------|----------|
| — User data per DP slave, max. | 244 byte |
| — Inputs, max.                 | 244 byte |
| — Outputs, max.                | 244 byte |
| — Slots, max.                  | 244      |
| — per slot, max.               | 128 byte |

### 4. Interface

|                           |                                                                  |
|---------------------------|------------------------------------------------------------------|
| Interface type            | Pluggable synchronization submodule (FO)                         |
| Plug-in interface modules | Synchronization modules 6ES7960-1AA06-0XA0 or 6ES7960-1AB06-0XA0 |

### 5. Interface

|                           |                                                                  |
|---------------------------|------------------------------------------------------------------|
| Interface type            | Pluggable synchronization submodule (FO)                         |
| Plug-in interface modules | Synchronization modules 6ES7960-1AA06-0XA0 or 6ES7960-1AB06-0XA0 |

### Protocols

#### Redundancy mode

##### Media redundancy

|                                        |        |
|----------------------------------------|--------|
| — Switchover time on line break, typ.  | 200 ms |
| — Number of stations in the ring, max. | 50     |

#### SIMATIC communication

- S7 routing Yes

#### Open IE communication

- TCP/IP Yes; via integrated PROFINET interface and loadable FBs
- Number of connections, max. 94

|                                                               |                                                                     |
|---------------------------------------------------------------|---------------------------------------------------------------------|
| — Data length, max.                                           | 32 kbyte                                                            |
| — several passive connections per port, supported             | Yes                                                                 |
| • ISO-on-TCP (RFC1006)                                        | Yes; Via integrated PROFINET interface or CP 443-1 and loadable FBs |
| — Number of connections, max.                                 | 94                                                                  |
| — Data length, max.                                           | 32 kbyte; 1 452 bytes via CP 443-1 Adv.                             |
| • UDP                                                         | Yes; via integrated PROFINET interface and loadable FBs             |
| — Number of connections, max.                                 | 94                                                                  |
| — Data length, max.                                           | 1 472 byte                                                          |
| <b>Web server</b>                                             |                                                                     |
| • supported                                                   | No                                                                  |
| <b>Isochronous mode</b>                                       |                                                                     |
| Equidistance                                                  | No                                                                  |
| <b>Communication functions</b>                                |                                                                     |
| PG/OP communication                                           | Yes                                                                 |
| • Number of connectable OPs without message processing        | 95                                                                  |
| • Number of connectable OPs with message processing           | 95; When using Alarm_S/SQ and Alarm_D/DQ                            |
| Data record routing                                           | Yes                                                                 |
| <b>Global data communication</b>                              |                                                                     |
| • supported                                                   | No                                                                  |
| <b>S7 basic communication</b>                                 |                                                                     |
| • supported                                                   | No                                                                  |
| <b>S7 communication</b>                                       |                                                                     |
| • supported                                                   | Yes                                                                 |
| • as server                                                   | Yes                                                                 |
| • as client                                                   | Yes                                                                 |
| • User data per job, max.                                     | 64 kbyte                                                            |
| • User data per job (of which consistent), max.               | 462 byte; 1 variable                                                |
| <b>S5 compatible communication</b>                            |                                                                     |
| • supported                                                   | Yes; (via CP max. 10 and FC AG_SEND and FC AG_RECV)                 |
| • User data per job, max.                                     | 8 kbyte                                                             |
| • User data per job (of which consistent), max.               | 240 byte                                                            |
| • Number of simultaneous AG-SEND/AG-RECV orders per CPU, max. | 64/64                                                               |
| <b>Standard communication (FMS)</b>                           |                                                                     |
| • supported                                                   | Yes; Via CP and loadable FB                                         |
| <b>Number of connections</b>                                  |                                                                     |
| • overall                                                     | 96                                                                  |
| • usable for PG communication                                 |                                                                     |

- reserved for PG communication
- adjustable for PG communication, max.
- usable for OP communication
  - reserved for OP communication
  - adjustable for OP communication, max.
- usable for S7 basic communication
  - reserved for S7 basic communication
  - adjustable for S7 basic communication, max.
- usable for S7 communication
  - reserved for S7 communication
  - adjustable for S7 communication, max.
- usable for routing
  - reserved for routing
  - adjustable for routing, max.

1  
0  
1  
0  
0  
0  
0  
0  
0  
0

### S7 message functions

|                                                                                                                                                              |                                                                                                                           |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Number of login stations for message functions, max.                                                                                                         | 95; Max. 95 with Alarm_S/SQ and Alarm_D/DQ (OPs); max. 16 with Alarm, Alarm_8, Alarm_8P, Notify and Notify_8 (e.g. WinCC) |
| Symbol-related messages                                                                                                                                      | No                                                                                                                        |
| SCAN procedure                                                                                                                                               | No                                                                                                                        |
| Program alarms                                                                                                                                               | Yes                                                                                                                       |
| Process diagnostic messages                                                                                                                                  | Yes                                                                                                                       |
| simultaneously active Alarm-S blocks, max.                                                                                                                   | 1 000; Simultaneously active alarm_S/SQ blocks or alarm_D/DQ blocks                                                       |
| Alarm 8-blocks <ul style="list-style-type: none"> <li>• Number of instances for alarm 8 and S7 communication blocks, max.</li> <li>• preset, max.</li> </ul> | 10 000<br>1 200                                                                                                           |
| Process control messages                                                                                                                                     | Yes                                                                                                                       |
| Number of archives that can log on simultaneously (SFB 37 AR_SEND)                                                                                           | 64                                                                                                                        |

### Test commissioning functions

|                                                                                                                                                             |                                                                                                             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| Status block                                                                                                                                                | Yes                                                                                                         |
| Single step                                                                                                                                                 | Yes                                                                                                         |
| Number of breakpoints                                                                                                                                       | 16                                                                                                          |
| <b>Status/control</b> <ul style="list-style-type: none"> <li>• Status/control variable</li> <li>• Variables</li> <li>• Number of variables, max.</li> </ul> | Yes; Up to 16 variable tables<br>Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters<br>70 |
| <b>Forcing</b> <ul style="list-style-type: none"> <li>• Forcing</li> </ul>                                                                                  | Yes                                                                                                         |

|                                                         |                                                |
|---------------------------------------------------------|------------------------------------------------|
| • Forcing, variables                                    | Inputs/outputs, bit memories, distributed I/Os |
| • Number of variables, max.                             | 512                                            |
| <b>Diagnostic buffer</b>                                |                                                |
| • present                                               | Yes                                            |
| • Number of entries, max.                               | 3 200                                          |
| — adjustable                                            | Yes                                            |
| — preset                                                | 120                                            |
| <b>Service data</b>                                     |                                                |
| • can be read out                                       | Yes                                            |
| <b>EMC</b>                                              |                                                |
| <b>Emission of radio interference acc. to EN 55 011</b> |                                                |
| • Limit class A, for use in industrial areas            | Yes                                            |
| • Limit class B, for use in residential areas           | No                                             |
| <b>Configuration</b>                                    |                                                |
| <b>Configuration software</b>                           |                                                |
| • STEP 7                                                | Yes                                            |
| <b>Programming</b>                                      |                                                |
| • Command set                                           | see instruction list                           |
| • Nesting levels                                        | 7                                              |
| • Access to consistent data in process image            | Yes                                            |
| • System functions (SFC)                                | see instruction list                           |
| • System function blocks (SFB)                          | see instruction list                           |
| <b>Programming language</b>                             |                                                |
| — LAD                                                   | Yes                                            |
| — FBD                                                   | Yes                                            |
| — STL                                                   | Yes                                            |
| — SCL                                                   | Yes                                            |
| — CFC                                                   | Yes                                            |
| — GRAPH                                                 | Yes                                            |
| — HiGraph®                                              | Yes                                            |
| <b>Number of simultaneously active SFCs</b>             |                                                |
| — RD_REC                                                | 8                                              |
| — WR_REC                                                | 8                                              |
| — WR_PARM                                               | 8                                              |
| — PARM_MOD                                              | 1                                              |
| — WR_DPARM                                              | 2                                              |
| — DPNRM_DG                                              | 8                                              |
| — RDSYSST                                               | 8                                              |
| — DP_TOPOL                                              | 1                                              |
| <b>Number of simultaneously active SFBs</b>             |                                                |
| — RDREC                                                 | 8                                              |

— WRREC

8

#### Know-how protection

- User program protection/password protection Yes
- Block encryption Yes; With S7 block Privacy

#### Dimensions

|        |        |
|--------|--------|
| Width  | 50 mm  |
| Height | 290 mm |
| Depth  | 219 mm |

#### Weights

Weight, approx. 995 g

**last modified:** 10/09/2020